

Concealed floor standing unit

FNQ-A



Home leave
operation

Designed to be concealed in walls

- › Ideal for installation in offices, hotels and residential applications
- › Blends unobtrusively with any interior décor: only the suction and discharge grills are visible
- › Its low height (620 mm) enables the unit to fit perfectly beneath a window
- › Requires very little installation space as the depth is only 200mm
- › High ESP allows flexible installation

FNQ-A + RXS-L/RXS-L3



Indoor unit		FNQ	25A	35A	50A	60A
Casing	Colour		Unpainted			
Dimensions	Unit	HeightxWidthxDepth	mm	620 / 720 (1)x790x200		620 / 720 (1)x1,190x200
Sound power level	Cooling		dBA	53		56
Sound pressure level	Cooling	High/Nom./Low	dBA	33/31/28		36/33/30
	Heating	High/Nom./Low	dBA	33/31/28		36/33/30
Control systems	Infrared remote control		BRC4C65			
	Wired remote control		BRC1D52 / BRC1E52A/B			

(1) Including installation legs


Efficiency data		FNQ + RXS	25A + 25L3	35A + 35L3	50A + 50L	60A + 60L
Cooling capacity	Nom.	kW	2.6	3.4	5.0	6.0
Heating capacity	Nom.	kW	3.20	4.00	5.80	7.00
Power input	Cooling	Nom.	kW	0.69	1.11	1.49
	Heating	Nom.	kW	0.80	1.15	1.74
Seasonal efficiency (according to EN14825)	Cooling	Pdesign	kW	2.60	3.40	5.00
		SEER		5.63	5.65	5.72
		Annual energy consumption	kWh	162	211	306
	Heating (Average climate)	Pdesign	kW	2.80	2.90	4.00
		SCOP/A		4.24	4.05	4.09
		Annual energy consumption	kWh	925	1,002	1,369
Nominal efficiency	EER		3.77	3.06	3.35	2.68
	COP		4.00	3.48	3.34	3.11
	Annual energy consumption	kWh	345	556	746	1,119

EER/COP according to Eurovent 2012, for use outside EU only

Outdoor unit				RXS	25L3	35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300	
Sound power level	Cooling			dBA	59	61	62	
	Heating			dBA	59	61	62	
Sound pressure level	Cooling	High/Low		dBA	46/43		48/44	49/46
	Heating	High/Low		dBA	47/44		48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~18			
Refrigerant	Type/Charge/GWP			kg/TCO ₂ eq	R-410A/1.0/2.1/2,087.5	R-410A/1.2/2.5/2,087.5	R-410A/1.7/3.5/2,087.5	R-410A/1.5/3.1/2,087.5
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240		1~/50/220-230-240	

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPE17-109

01/17



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.