



VRV IV S-series heat pump Air Conditioning Technical Data RXYSQ-TY1



RXYSQ8TMY1B
RXYSQ10TMY1B
RXYSQ12TMY1B

TABLE OF CONTENTS

RXYSQ-TY1

1	Features	4
	RXYSQ-TY1	4
2	Specifications	5
3	Options	8
4	Combination table	9
5	Capacity tables	11
	Capacity Table Legend	11
	Capacity Correction Factor	12
6	Dimensional drawings	15
7	Centre of gravity	16
8	Piping diagrams	18
9	Wiring diagrams	19
	Wiring Diagrams - Three Phase	19
10	External connection diagrams	20
11	Sound data	21
	Sound Power Spectrum	21
	Sound Pressure Spectrum	23
12	Installation	25
	Installation Method	25
	Refrigerant Pipe Selection	29
13	Operation range	31
14	Appropriate Indoors	32

1 Features

1 - 1 RXYSQ-TY1

1

- › Space saving trunk design for flexible installation
- › Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains
- › Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Perfera ...
- › Wide range of units (4 to 12HP) suitable for projects up to 200m² with space limitations
- › Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature and full inverter compressors
- › Customize your VRV for best seasonal efficiency & comfort with the weather dependant Variable Refrigerant Temperature function. Increased seasonal efficiency with up to 28%. No more cold draft by supply of high outblow temperatures
- › VRV configurator software for the fastest and most accurate commissioning, configuration and customisation
- › 3 steps in night quiet mode: step 1: 47dBA, step 2: 44 dBA, step 3: 41 dBA
- › Possibility to limit peak power consumption between 30 and 80%, for example during periods with high power demand
- › Connectable to all VRV control systems
- › Keep your system in top condition via the Daikin Cloud Service: 24/7 monitoring for maximum efficiency, extended lifetime and immediate service support thanks to failure prediction



Inverter

2 Specifications

1 - 1 RXYSQ-TY1

Technical Specifications					RXYSQ8TY1		RXYSQ10TY1		RXYSQ12TY1			
Recommended combination					4 x FXMQ50P7VEB		4 x FXMQ63P7VEB		6 x FXMQ50P7VEB			
Cooling capacity	Prated,c				kW	22.4 (1)	28.0 (1)		33.5 (1)			
		Test setup 1	35°C AHRI	Btu/h	76,400 (2)	95,500 (2)		114,300 (2)				
			35°C AHRI	kW	22.4 (2)	28.0 (2)		33.5 (2)				
			46°C ISO	Btu/h	58,000 (3)	68,200 (3)		81,850 (3)				
			46°C ISO	kW	17.0 (3)	20.0 (3)		24.0 (3)				
			48°C AHRI	Btu/h	51,150 (4)	58,000 (4)		68,200 (4)				
Heating capacity	Nom.	6°CWB			kW	22.4 (5)	28.0 (5)		33.5 (5)			
		Prated,h			kW	22.4 (5)	28.0 (5)		33.5 (5)			
Power input - 50Hz	Cooling	Test setup 1	35°C AHRI	kW	6.78 (2)	8.54 (2)		10.20 (2)				
			46°C ISO	kW	5.80 (3)	7.02 (3)		8.60 (3)				
			48°C AHRI	kW	5.34 (4)	6.80 (4)		7.97 (4)				
	Heating	Nom.	6°CWB			kW	5.82 (5)	6.60 (5)		8.19 (5)		
			Test setup 1	35°C AHRI	Btu/h/W	11.30 (2)	11.20 (2)					
				35°C AHRI	kW/kW	3.30 (2)	3.28 (2)					
46°C ISO	Btu/h/W	10.00 (3)		9.72 (3)		9.52 (3)						
46°C ISO	kW/kW	2.93 (3)		2.85 (3)		2.79 (3)						
48°C AHRI	Btu/h/W	9.58 (4)		8.53 (4)		8.56 (4)						
COP at nom. capacity	Test setup 1	6°CWB			kW/kW	3.85	4.24		4.09			
		6°CWB			Btu/h/W	-						
		6°CWB			kW/kW	-						
		CSPF					-					
		SCOP					4.2		4.1		4.3	
		SEER					6.3				6.5	
ηs,c					%	247.3	247.4		256.5			
ηs,h					%	165.8	162.4		169.6			
Space cooling	A Condition (35°C - 27/19)	EERd Pdc				kW	2.6	2.8		2.7		
						kW	22.4	28.0		33.5		
			4.2					4.3				
			16.5					20.6		24.7		
			7.7							7.9		
			10.6					13.3		15.9		
			13.7					12.2		13.6		
			6.4					7.1		7.3		
Space heating (Average climate)	TBivalent	COPd (declared COP)				2.4	2.2					
		Pd _h (declared heating cap)				kW	14.9	19.6		23.5		
		Tb _{iv} (bivalent temperature)				°C	-10					
	TOL	COPd (declared COP)				2.4	2.2					
		Pd _h (declared heating cap)				kW	14.9	19.6		23.5		
		Tol (temperature operating limit)				°C	-10					
	A Condition (-7°C)	COPd (declared COP)				2.6	2.4					
		Pd _h (declared heating cap)				kW	13.2	17.4		20.8		
	B Condition (2°C)	COPd (declared COP)				4.0	4.1		4.3			
		Pd _h (declared heating cap)				kW	8.0	10.6		12.7		
	C Condition (7°C)	COPd (declared COP)				5.9				6.3		
		Pd _h (declared heating cap)				kW	5.0	6.8		8.1		
	D Condition (12°C)	COPd (declared COP)				7.8	6.3		6.7			
		Pd _h (declared heating cap)				kW	5.8	6.4		6.6		
Capacity range					HP	8	10		12			
PED	Category				Category II							
	Most critical part	Name			Accumulator							
Ps*V		Bar*l			202	279						
Maximum number of connectable indoor units					64 (6)							
Indoor index connection	Min.				100.0		125.0		150.0			
	Max.				260.0		325.0		390.0			

2 Specifications

1 - 1 RXYSQ-TY1

Technical Specifications					RXYSQ8TY1		RXYSQ10TY1		RXYSQ12TY1		
Dimensions	Unit	Height	mm		1,430		1,615				
		Width	mm				940				
		Depth	mm		320		460				
	Packed unit	Height	mm		1,615		1,745				
		Width	mm		1,030		1,015				
		Depth	mm		420		575				
Weight	Unit	kg		144		175		180			
	Packed unit	kg		158		191		196			
Packing	Material				Carton						
	Weight	kg			5.6		8.2				
Packing 2	Material				Wood						
	Weight	kg			5.5		8.8				
Packing 3	Material				Plastic						
	Weight	kg			0.3		0.4				
Casing	Colour				Daikin White						
	Material				Painted galvanized steel plate						
Heat exchanger	Type				Cross fin coil						
	Indoor side				Air						
	Outdoor side				Air						
	Air flow rate	Cooling	Rated	m³/h	8,400		10,920				
		Heating	Rated	m³/h	8,400		10,920				
Fan	Quantity				2						
Fan motor	Quantity				2						
	Type				DC motor						
	Output	W			200						
Compressor	Quantity				1						
	Type				Hermetically sealed scroll compressor						
	Crankcase heater	W			33						
Operation range	Cooling	Min.	°CDB		-5.0						
		Max.	°CDB		52.0						
	Heating	Min.	°CWB		-20.0						
		Max.	°CWB		15.5						
Sound power level	Cooling	Nom.	dBA		73.0 (7)		74.0 (7)		76.0 (7)		
	Heating	Prated,h	dBA		73.0 (7)		74.0 (7)		76.0 (7)		
Sound pressure level	Cooling	Nom.	dBA		55.0 (8)				57.0 (8)		
Refrigerant	Type				R-410A						
	GWP				2,087.5						
	Charge	TCO2Eq			11.5		14.6		16.7		
Refrigerant oil	Charge	kg			5.5		7.0		8.0		
	Type				Synthetic (ether) oil FVC68D						
Piping connections	Liquid	Type			Braze connection						
		OD	mm		10				13		
	Gas	Type			Braze connection						
		OD	mm		19.1		22.2		25.4		
Capacity control	Total piping length	System	Actual	m	300 (9)						
	Method				Inverter controlled						
Indication if the heater is equipped with a supplementary heater					no						
Supplementary heater	Back-up capacity	Heating	elbu	kW	0.0						
Power consumption in other than active mode	Crank-case heater mode	Cooling	PCK	kW	0.000						
		Heating	PCK	kW	0.040		0.046				
	Off mode	Cooling	POFF	kW	0.035		0.046				
		Heating	POFF	kW	0.040		0.046				
	Standby mode	Cooling	PSB	kW	0.035		0.046				
Power consumption in other than active mode	Standby mode	Heating	PSB	kW	0.040		0.046				
	Thermo-stat-off mode	Cooling	PTO	kW	0.015		0.013				
		Heating	PTO	kW	0.055		0.059				
Cooling	Cdc (Degradation cooling)				0.25						
Heating	Cdh (Degradation heating)				0.25						
Safety devices	Item	01				High pressure switch					
		02				Fan driver overload protector					
		03				Inverter overload protector					
		04				PC board fuse					

Standard accessories: Installation manual; Quantity: 1;

Standard accessories: Operation manual; Quantity: 1;

2 Specifications

1 - 1 RXYSQ-TY1

Standard accessories: Connection pipes; Quantity: 1;

Electrical Specifications			RXYSQ8TY1	RXYSQ10TY1	RXYSQ12TY1
Power supply	Name		Y1		
	Phase		3N~		
	Frequency	Hz	50		
	Voltage	V	380-415		
Power supply intake			Both indoor and outdoor unit		
Voltage range	Min.	%	-10		
	Max.	%	10		
Current	Nominal	Cooling	9.6 (10)		
	running current (RLA)	A	10.7 (10)		
Current - 50Hz	Starting current (MSC) - remark		See note 11		
	Zmax	List	No requirements		
	Minimum Ssc value	kVa	564 (12)		
	Minimum circuit amps (MCA)	A	615 (12)		
	Maximum fuse amps (MFA)	A	22.0 (13)		
	Total overcurrent amps (TOCA)	A	25 (14)		
	Full load	Total	16.5 (15)		
	amps (FLA)	A	25.0 (15)		
Wiring connections - 50Hz	For power supply	Quantity	5G		
	For connection with indoor	Quantity	2		
		Remark	F1,F2		

- (1)Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 7.5m; level difference: 0m |
- (2)Cooling: T1: indoor temp. 26,7°CDB, 19,4°CWB, outdoor temp. 35°CDB, AHRI 1230:2010, power input indoor units (duct type) included |
- (3)Cooling: T3: indoor temp. 29,0°CDB, 19,0°CWB, outdoor temp. 46°CDB, ISO15042:2011, power input indoor units (duct type) included |
- (4)Cooling: T2: indoor temp. 26,6°CDB, 19,4°CWB, outdoor temp. 48°CDB, AHRI 1230:2010, power input indoor units (duct type) included |
- (5)Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 7.5m; level difference: 0m |
- (6)Actual number of units depends on the indoor unit type (VRV DX indoor, RA DX indoor, etc.) and the connection ratio restriction for the system (being; 50% ≤ CR ≤ 130%). |
- (7)Sound power level is an absolute value that a sound source generates. |
- (8)Sound pressure level is a relative value, depending on the distance and acoustic environment. For more details, please refer to the sound level drawings. |
- (9)Refer to refrigerant pipe selection or installation manual |
- (10)RLA is based on following conditions: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB |
- (11)MSC means the maximum current during start up of the compressor. This unit uses only inverter compressors. Starting current is always ≤ max. running current. |
- (12)In accordance with EN/IEC 61000-3-12, it may be necessary to consult the distribution network operator to ensure that the equipment is connected only to a supply with Ssc ≥ minimum Ssc value |
- (13)MCA must be used to select the correct field wiring size. The MCA can be regarded as the maximum running current. |
- (14)MFA is used to select the circuit breaker and the ground fault circuit interrupter (earth leakage circuit breaker). |
- (15)TOCA means the total value of each OC set. |
- (16)FLA means the nominal running current of the fan |
- (17)Maximum allowable voltage range variation between phases is 2%. |
- (18)Voltage range: units are suitable for use on electrical systems where voltage supplied to unit terminal is not below or above listed range limits. |
- (19)The automatic ESEER value corresponds with normal VRV IV-S heat pump operation, including the advanced energy saving functionality (variable refrigerant temperature control). |
- (20)The standard ESEER value corresponds with normal VRV IV-S heat pump operation, not taking into account the advanced energy saving functionality. |
- (21)Sound values are measured in a semi-anechoic room. |
- (22)EN/IEC 61000-3-12: European/international technical standard setting the limits for harmonic currents produced by equipment connected to public low-voltage system with input current > 16A and ≤ 75A per phase |
- (23)Ssc: Short-circuit power |
- (24)For detailed contents of standard accessories, see installation/operation manual

3 Options

3 - 1 Options

RXYSQ-TY1

VRV4-S Heat pump Option list

Nr.	Item	RXYSQ4~6TMV1B	RXYSQ4~6T7V1B RXYSQ4~6T8VB(9)	RXYSQ4~6T7Y1B RXYSQ4~6T8YB(9)	RXYSQ8~12TMY1B	RXYSQ6T7Y1B9 RXYSQ6T8Y1B9	RXYSQ6TMYFK
I.	Refnet header	-	-	-	KHRQ22M64H	-	KHRQ22M64H
II.	Refnet joint	-	-	-	KHRQ22M29T9	-	KHRQ22M29T9
1a.	Cool/heat selector (switch)	-	KRC19-26	-	KRC19-26	-	-
1b.	Cool/heat selector (fixing box)	-	KJB111A	-	KJB111A	-	-
1c.	Cool/heat selector (PCB)	-	EBRP2B	-	-	-	-
1d.	Cool/heat selector (cable)	-	-	EKCHSC	-	EKCHSC	-
2.	Drain plug kit	-	EKDK04	-	EKDK04	-	-
3.	VRV configurator	-	-	-	-	-	-
4.	Demand PCB	-	-	-	-	-	-
5.	Branch provider - ·2· rooms	-	BPMKS967A2	-	-	-	-
6.	Branch provider - ·3· rooms	-	BPMKS967A3	-	-	-	-

Notes

- All options are kits
- To mount option ·1a·, option ·1b· is required.
- For ·RXYSQ4~6T7V1B·
For ·RXYSQ4~6T8VB·
To operate the cool/heat selector function, options ·1a· and ·1c· are both required.
- For ·RXYSQ4~6T7Y1B·
For ·RXYSQ4~6T8YB·
To operate the cool/heat selector function, options ·1a· and ·1d· are both required.

3D097778E

4 Combination table

4 - 1 Combination Table

RXYSQ-TY1

VRV4-S Heat pump Indoor unit combination restrictions

Combination table	RXYSCQ4~6TMV1B	RXYSQ4~6T7V1B	RXYSQ4~6T7Y1B	RXYSQ8~12TMY1B
·VRV* DX· indoor unit	O	O	O	O
·RA DX· indoor unit	O	O	O	O
Hydrobox unit	X	X	X	X
Air handling unit (AHU) ⁽²⁾	O	O	O	O

O: Allowed

X: Not allowed

Notes

(2) The following units are considered AHUs:

- ·EKEXV + EKEQ(MA/FA) + AHU· coil
- ·Biddle· air curtain
- ·FXMQ_MF· units

3D097983A

RXYSQ-TY1

VRV4-S Heat pump Indoor unit combination restrictions

Indoor unit combination pattern	·VRV* DX· indoor unit	·RA DX· indoor unit	Hydrobox unit	Air handling unit (AHU) ⁽¹⁾
·VRV* DX· indoor unit	O	X	X	O
·RA DX· indoor unit	X	O	X	X
Hydrobox unit	X	X	X	X
Air handling unit (AHU) ⁽¹⁾	O	X	X	O ₁

O: Allowed

X: Not allowed

Notes

1. O₁

- Combination of ·AHU· only + control box ·EKEQFA· (not combined with ·VRV DX· indoor units)

→ ·X·-control is possible [·EKEXV+EKEQFA*· boxes]. No Variable Refrigerant Temperature control possible.

→ ·Y·-control is possible [·EKEXV+EKEQFA*· boxes]. No Variable Refrigerant Temperature control possible.

→ ·W·-control is possible [·EKEXV+EKEQFA*· boxes]. No Variable Refrigerant Temperature control possible.

- Combination of ·AHU· only + control box ·EKEQMA· (not combined with ·VRV DX· indoor units)

→ Z-control is possible (the allowed number of [·EKEXV + EKEQMA· boxes] is determined by the connection ratio (·90-110%·) and the capacity of the outdoor unit).

2. Combination of ·AHU· and ·VRV DX· indoor units

→ Z-control is possible (·EKEQMA*· boxes are allowed, but with a limited connection ratio).

3. (1) The following units are considered AHUs:

- ·EKEXV + EKEQ(MA/FA) + AHU· coil
- ·Biddle· air curtain
- ·FXMQ_MF· units

Information

- ·VKM· units are considered regular ·VRV DX· indoor units.

3D097983A

4 Combination table

4 - 1 Combination Table

RXYSQ-TY1

4

Unit combination restrictions: ·VRV4· outdoor units (all models) + ·15·-class indoor units

Units in scope: ·FXZQ15A· and ·FXAQ15A·.

- In case the system contains these indoor units and the total connection ratio (·CR·) ≤ ·100·%: no special restrictions. Follow the restrictions that apply to regular ·VRV DX· indoor units.
- In case the system contains these indoor units and the total connection ratio (·CR·) > ·100·%: special restrictions apply.
 - When the connection ratio (·CR1·) of the sum of all ·FXZQ15A· and/or ·FXAQ15A· units in the system ≤ ·70·%, and ALL other ·VRV DX· indoor units have an individual capacity class > ·50·: no special restrictions.
 - When the connection ratio (·CR1·) of the sum of all ·FXZQ15A· and/or ·FXAQ15A· units in the system ≤ ·70·%, and NOT ALL other ·VRV DX· indoor units have an individual capacity class > ·50·: the restrictions below apply.
 - ° 100% < CR ≤ 105% -> ·CR1· of the sum of all ·FXZQ15A· and/or ·FXAQ15A· indoor units in the system must be ≤ ·70·%.
 - ° 105% < CR ≤ 110% -> ·CR1· of the sum of all ·FXZQ15A· and/or ·FXAQ15A· indoor units in the system must be ≤ ·60·%.
 - ° 110% < CR ≤ 115% -> ·CR1· of the sum of all ·FXZQ15A· and/or ·FXAQ15A· indoor units in the system must be ≤ ·40·%.
 - ° 115% < CR ≤ 120% -> ·CR1· of the sum of all ·FXZQ15A· and/or ·FXAQ15A· indoor units in the system must be ≤ ·25·%.
 - ° 120% < CR ≤ 125% -> ·CR1· of the sum of all ·FXZQ15A· and/or ·FXAQ15A· indoor units in the system must be ≤ ·10·%.
 - ° 125% < CR ≤ 130% -> ·FXZQ15A· and ·FXAQ15A· cannot be used.

Remark

Only the ·15·-class indoor units explicitly mentioned on this page are in scope. Other indoor units follow the rules that apply to regular ·VRV DX· indoor units.

3D104665A

RXYSQ-TY1

RXYSQ-TY9

RXYSQ-TV9

RXYSQ-TV1

VRV4-S
Heat pump
·RA/SA DX· indoor unit
Compatibility list

Configuration		Indoor unit type
·RA· indoor unit	Wall-mounted	Emura
		FTX120M (W/S)
		FTX125M (W/S)
		FTX135M (W/S)
		FTX150M (W/S)
		FTXM20N
		FTXM20R
		FTXM25N
		FTXM25R
		FTXM35N
	FTXM	FTXM35R
		FTXM42N
		FTXM42R
		FTXM50N
		FTXM50R
		FTXM60N
		FTXM60R
		FTXM71N
		FTXM71R
	CTXM	CTXM15N
	Stylish	CTXM15R
		FTXA20
		FTXA25
		FTXA35
		FTXA42
		FTXA50
	Floor-standing	FLXS25B
	Ceiling-mounted	FLXS35B
		FLXS50B
		FLXS60B
		FLXS60B
·SA· indoor unit	Floor-standing	FVXM
		FVXM25F
		FVXM35F
		FVXM50F
		FVXM50F
		CVXM20A
		FVXM25A
		FVXM35A
		FVXM50A
		FVXM50A
	Nexura	FVXG25K
		FVXG35K
		FVXG50K
	Duct	FDXM25F
		FDXM35F
		FDXM50F
		FDXM60F
		FDXM60F

Configuration		Indoor unit type
Cassette	Fully Flat 2x2	FFA25A
		FFA35A
		FFA50A
		FFA60A
	Roundflow 3x3	FCAG35A
		FCAG50A
		FCAG60A
		FCAG71A
		FCAG71A
		FCAG71A
Ceiling-suspended	FHA	FHA35A
		FHA50A
		FHA60A
		FHA71A
		FHA71A
	FBA	FBA35A
		FBA50A
		FBA60A
		FBA71A
		FBA71A
Duct	FNA	FNA25A
		FNA35A
		FNA50A
		FNA60A

Remark

- The limitations on the use of ·RA/SA· indoor units with the ·VRV4-S· Heat Pump are subject to the rules set out in drawings ·3D097983· and ·3D097984·.

3D097777H


5 Capacity tables

5 - 1 Capacity Table Legend

In order to fulfill more your requirements on quick access of data in the format you require, we have developed a tool to consult capacity tables.

Below you can find the link to the capacity table database and an overview of all the tools we have to help you select the correct product:

- **Capacity table database:** lets you find back and export quickly the capacity information you are looking for based upon unit model, refrigerant temperature and connection ratio.
- You can access the capacity table viewer here:
https://my.daikin.eu/content/denv/en_US/home/applications/software-finder/capacity-table-viewer.html



- An overview of **all software tools** that we offer can be found here:
https://my.daikin.eu/denv/en_US/home/applications/software-finder.html



5 Capacity tables

5 - 2 Capacity Correction Factor

RXYSQ-TY1

MINI VRV

Integrated heating capacity coefficient

The heating capacity tables do not take into account the capacity reduction in case of frost accumulation or defrost operation.
The capacity values that take these factors into account, or in other words, the integrated heating capacity values, can be calculated as follows:


Formula

A = Integrated heating capacity
B = Capacity characteristics value
C = Integrated correction factor for frost accumulation (see table)

$$A = B \cdot C$$

Inlet air temperature of heat exchanger

[°CDB/°CWB]	-7/-7.6	-5/-5.6	-3/-3.7	0/-0.7	3/2.2	5/4.1	7/6
RXYSQ4TMV1B							
RXYSQ5TMV1B							
RXYSQ6TMV1B							
RXYSQ4T7V1B							
RXYSQ5T7V1B							
RXYSQ6T7V1B							
RXYSQ4T7Y1B							
RXYSQ5T7Y1B							
RXYSQ6T7Y1B							
RXYSQ6T7Y1B9							
RXYSQ4T8VB							
RXYSQ5T8VB	0,88	0,86	0,80	0,75	0,76	0,82	1,00
RXYSQ6T8VB							
RXYSQ4T8YB							
RXYSQ5T8YB							
RXYSQ6T8YB							
RXYSQ6T8Y1B9							
RXYSQ4T8VB9							
RXYSQ5T8VB9							
RXYSQ6T8VB9							
RXYSQ4T8YB9							
RXYSQ5T8YB9							
RXYSQ6T8YB9							
RXYSQ8TMY1B	0,95	0,93	0,88	0,84	0,85	0,90	1,00
RXYSQ10TMY1B	0,95	0,93	0,87	0,79	0,80	0,88	1,00
RXYSQ6TMYFK	0,95	0,93	0,87	0,79	0,80	0,88	1,00
RXYSQ12TMY1B	0,95	0,92	0,87	0,75	0,76	0,85	1,00



Notes


- (1) The figure shows the integrated heating capacity for a single cycle (from one defrost operation to the next).
- (2) When there is an accumulation of snow against the outdoor unit heat exchanger, there will always be a temporary reduction in capacity depending on the outdoor temperature (°C DB), relative humidity (RH) and the amount of frosting which occurs.

3D09659D

5 Capacity tables

5 - 2 Capacity Correction Factor

RXYSQ8TY1



Notes

- These figures illustrate the capacity correction factor due to the piping length for a standard indoor unit system at maximum load (with the thermostat set to maximum), under standard conditions. Moreover, under partial load conditions, there is only a minor deviation for the capacity correction ratio, as shown in the above figures.
- With this outdoor unit, the following control is used:- in case of cooling: constant evaporating pressure control- in case of heating: constant condensing pressure control

3. Method of calculating the capacity of the outdoor units.

The maximum capacity of the system will be either the total capacity of the indoor units or the maximum capacity of the outdoor units as mentioned below, whichever is less.

Indoor connection ratio ≤ 100%.

$$\text{Maximum capacity of outdoor units} = \text{Capacity of outdoor units from capacity table at 100\% connection ratio.} \times \text{Correction ratio of piping to furthest indoor unit}$$

Indoor connection ratio > 100%.

$$\text{Maximum capacity of outdoor units} = \text{Capacity of outdoor units from capacity table at installed connection ratio.} \times \text{Correction ratio of piping to furthest indoor unit}$$

- When the overall equivalent piping length is 90 m or more, the diameter of the main gas pipes (outdoor unit - branch sections) must be increased. For the new diameters, see below.

Model	Standard liquid side Ø	Increased liquid side Ø	Standard gas side Ø	Increased gas side Ø
RXYSQ8TY1B	9,5	12,7	19,1	22,2

5. Overall equivalent length


$$\text{Overall equivalent length} = \text{Equivalent length of the main pipe} \times \text{Correction factor} + \text{Equivalent length of the branch pipes}$$

Choose the correction factor from the following table.

When calculating the cooling capacity: gas pipe size

When calculating the heating capacity: liquid pipe size

	Standard size	Size increase
Cooling (gas pipe)	1,0	0,5
Heating (liquid pipe)	1,0	0,3



Overall equivalent length


- Cooling mode = 80 m x 0,5 + 40 m = 80 m
- Heating mode = 80 m x 0,3 + 40 m = 64 m

Capacity correction ratio (height difference = 0)

- Cooling mode = 0,87
- Heating mode = 1,00

3D094660D

RXYSQ10TY1



Notes

- These figures illustrate the capacity correction factor due to the piping length for a standard indoor unit system at maximum load (with the thermostat set to maximum), under standard conditions. Moreover, under partial load conditions, there is only a minor deviation for the capacity correction ratio, as shown in the above figures.
- With this outdoor unit, the following control is used:- in case of cooling: constant evaporating pressure control- in case of heating: constant condensing pressure control

3. Method of calculating the capacity of the outdoor units.

The maximum capacity of the system will be either the total capacity of the indoor units or the maximum capacity of the outdoor units as mentioned below, whichever is less.

Indoor connection ratio ≤ 100%.

$$\text{Maximum capacity of outdoor units} = \text{Capacity of outdoor units from capacity table at 100\% connection ratio.} \times \text{Correction ratio of piping to furthest indoor unit}$$

Indoor connection ratio > 100%.

$$\text{Maximum capacity of outdoor units} = \text{Capacity of outdoor units from capacity table at installed connection ratio.} \times \text{Correction ratio of piping to furthest indoor unit}$$

- When the overall equivalent piping length is 90 m or more, the diameter of the main gas pipes (outdoor unit - branch sections) must be increased. For the new diameters, see below.

Model	Standard liquid side Ø	Increased liquid side Ø	Standard gas side Ø	Increased gas side Ø
RXYSQ10TY1B	9,5	12,7	22,2	25,4 *

* If not available on-site, do not increase the piping diameter.

If not increased, do not apply a correction factor to the equivalent piping length (see note 5).

5. Overall equivalent length


$$\text{Overall equivalent length} = \text{Equivalent length of the main pipe} \times \text{Correction factor} + \text{Equivalent length of the branch pipes}$$

Choose the correction factor from the following table.

When calculating the cooling capacity: gas pipe size

When calculating the heating capacity: liquid pipe size

	Standard size	Size increase
Cooling (gas pipe)	1,0	0,5
Heating (liquid pipe)	1,0	0,2



Overall equivalent length

- Cooling mode = 80 m x 0,5 + 40 m = 80 m
- Heating mode = 80 m x 0,2 + 40 m = 56 m

Capacity correction ratio (height difference = 0)

- Cooling mode = 0,87
- Heating mode = 0,99


3D094660D

5 Capacity tables

5 - 2 Capacity Correction Factor


RXYSQ12TY1

Correction ratio for cooling capacity



x-axis : Equivalent piping length [m]
y-axis : Height difference between outdoor unit and furthest indoor unit [m]

Correction ratio for heating capacity



x-axis : Equivalent piping length [m]
y-axis : Height difference between outdoor unit and furthest indoor unit [m]

Notes

- These figures illustrate the capacity correction factor due to the piping length for a standard indoor unit system at maximum load (with the thermostat set to maximum), under standard conditions. Moreover, under partial load conditions, there is only a minor deviation for the capacity correction ratio, as shown in the above figures.
- With this outdoor unit, the following control is used:- in case of cooling: constant evaporating pressure control- in case of heating: constant condensing pressure control

3. Method of calculating the capacity of the outdoor units.

The maximum capacity of the system will be either the total capacity of the indoor units or the maximum capacity of the outdoor units as mentioned below, whichever is less.

Indoor connection ratio ≤ 100%.

Maximum capacity of outdoor units = Capacity of outdoor units from capacity table at 100% connection ratio. x Correction ratio of piping to furthest indoor unit

Indoor connection ratio > 100%.

Maximum capacity of outdoor units = Capacity of outdoor units from capacity table at installed connection ratio. x Correction ratio of piping to furthest indoor unit

- When the overall equivalent piping length is 90 m or more, the diameter of the main gas pipes (outdoor unit - branch sections) must be increased. For the new diameters, see below.

Model	Standard liquid side Ø	Increased liquid side Ø	Standard gas side Ø	Increased gas side Ø
RXYSQ8TMY1B	12,7	15,9	25,4	28,6

5. Overall equivalent length

Overall equivalent length = Equivalent length of the main pipe x Correction factor + Equivalent length of the branch pipes


Choose the correction factor from the following table.

When calculating the cooling capacity: gas pipe size

When calculating the heating capacity: liquid pipe size

	Standard size	Size increase
Cooling (gas pipe)	1,0	0,5
Heating (liquid pipe)	1,0	0,3

Example



Overall equivalent length

- Cooling mode = 80 m x 0,5 + 40 m = 80 m
- Heating mode = 80 m x 0,2 + 40 m = 64 m

Capacity correction ratio (height difference = 0)


- Cooling mode = 0,92
- Heating mode = 1,00

3D094660D

7 Centre of gravity

7 - 1 Centre of Gravity

RXYSQ8TY1




4D098084

7 Centre of gravity

7 - 1 Centre of Gravity

RXYSQ10-12TY1




4D098085

8 Piping diagrams


8 - 1 Piping Diagrams

8

RXYSQ8TY1



RXYSQ10-12TY1




9 Wiring diagrams


9 - 1 Wiring Diagrams - Three Phase

RXYSQ8TY1

- A1P : Printed circuit board (Main)
- A2P : Printed circuit board (Noise filter)
- A3P : Printed circuit board (INV)
- A4P : Printed circuit board (Fan 1)
- A5P : Printed circuit board (Fan 2)
- B51-B55 : Push button switch (Mode, set, return, test, reset)
- C32, C67 : Capacitor
- DS1 : Dip switch
- E1HC : Crankcase heater
- F101U : Fuse (SA, DC650V) (A4P) (A5P)
- F1U, F2U : Fuse (T 3.15A / 250V) (A1P)
- F400U : Fuse (T 6.3A / 250V) (A2P)
- H1P-H8P : Pilot lamp (service monitor-orange) (H2P) Prepare, Test ----- Flickering Malfunction Detection - Light up
- K1P : Pilotlamp (service monitor - green)
- K2M : Magnetic relay (A3P)
- K3R : Magnetic contactor (M1C) (A3P)
- K3R : Magnetic relay (A2P)
- K3R : Magnetic relay (Y15)
- K5R : Magnetic relay (Y35)
- K7R : Magnetic relay (E1HC)
- L1R : Reactor
- M1C : Motor (compressor)
- M1F, M2F : Motor (fan)
- PS : Switching power supply (A1P) (A3P)
- Q1RP : Reverse phase protector
- R24 : Resistor (current sensor) (A4P) (A5P)
- R2, R3 : Resistor
- R95 : Resistor (current limiting)
- R1T : Thermistor (Air)
- R2T : Thermistor (Suction)
- R3T : Thermistor (M1C Discharge)
- R4T : Thermistor (heat exchanger deicer)
- R5T : Thermistor (heat exchanger outlet)
- R6T : Thermistor (Liquid pipe)
- R7T : Thermistor (Accumulator)
- S1NPH : Pressure sensor (High)
- S1NPL : Pressure sensor (low)
- S1PH : High pressure switch
- V1CP : Safety devices input
- V1R : IGBT Module (A4P) (A5P)
- V1R : Diode bridge IGBT Module (A3P)
- X1A, X2A : Connector (M1F)
- X3A, X4A : Connector (M2F)
- X1M : Terminal strip (Power supply)
- X1M : Terminal strip (Control) (A1P)
- Y1E : Electronic expansion valve (Main)
- Y2E : Electronic expansion valve (Subcool)
- Y1S : Solenoid valve (hot gas)
- Y3S : Solenoid valve (4 way valve)
- Z1C-8C : Noise filter (ferrite core)
- Z1F : Noise filter (with surge absorber)



- Notes:
- 1 Lay-out, illustrations and letter size = this drawing.
 - 2 Printing: Silkscreen printing black
 - 3 Add a slit on the backside of the sticker.



- 4 Unspecified tolerances: +/- 1
- 5 For material specifications refer to: AD150142


Notes:

1. This wiring diagram only applies to the outdoor unit.
2. Field wiring
3. Terminal, Connector, Movable connector, Fixed connector, Terminal strip, Protective earth (screw), Noiseless earth
4. Refer to the installation manual, for connection wiring to indoor-outdoor transmission F1 - F2, outdoor-outdoor transmission F1 - F2.
5. Refer to 'installation manual' (on back front plate). How to use BS1-B55 and DS1 switch.
6. When operating, do not short circuit for protection device. (S1PH)
7. Colours: BLK: Black, RED: Red, BLU: Blue, WHT: White, GRN: Green, BRN: Brown, YLW: Yellow


2D094434D

RXYSQ10-12TY1

- A1P : Printed circuit board (Main)
- A2P : Printed circuit board (Noise filter)
- A3P : Printed circuit board (INV)
- A4P : Printed circuit board (Fan 1)
- A5P : Printed circuit board (Fan 2)
- B51-B55 : Push button switch (Mode, Set, Return)
- C47, C48 : Capacitor (A3P)
- DS1, DS2 : Dip switch (A1P)
- E1HC : Crankcase heater
- F1U, F2U : Fuse (T 3.15A / 250V) (A1P)
- F101U : Fuse (A4P) (A5P)
- F411U-F412U : Fuse (A2P)
- F601U : Fuse (A3P)
- HAP : Pilotlamp (service monitor - green) (A1P) (A3P) (A4P) (A5P)
- K1M : Magnetic contactor (A3P)
- K1R : Magnetic relay (A3P)
- K3R : Magnetic relay (A3P)
- K4R : Magnetic relay (Y25) (A1P)
- K7R : Magnetic relay (E1HC) (A1P)
- K11R : Magnetic relay (Y15) (A1P)
- L1R : Reactor
- M1C : Motor (compressor)
- M1F, M2F : Motor (fan)
- PS : Switching power supply (A1P) (A3P)
- Q1LD : Leakage detection circuit (A1P)
- Q1RP : Phase reversal detect circuit (A1P)
- R1T : Thermistor (Air) (A1P)
- R21T : Thermistor (M1C Discharge)
- R3T : Thermistor (Accumulator)
- R4T : Thermistor (Heat exchanger liq. Pipe)
- R5T : Thermistor (Subcool liq. Pipe)
- R6T : Thermistor (Heat exchanger gas pipe)
- R7T : Thermistor (heat exchanger deicer)
- R8T : Thermistor (M1C body)
- R1 : Resistor (current limiting) (A3P)
- R24 : Resistor (current sensor) (A4P)
- R313 : Resistor (current sensor) (A3P)
- R865, R867 : Resistor (A3P)
- S1NPH : Pressure sensor (High)
- S1NPL : Pressure sensor (low)
- S1PH : High pressure switch
- SEG1-SEG3 : 7-segment display (A1P)
- T1A : current sensor
- V1R : Power module (A3P) (A4P) (A5P)
- V2R : Power module (A3P)
- X1A, X2A : Connector (M1F)
- X3A, X4A : Connector (M2F)
- X1M : Terminal block (Power supply)
- X1M : Terminal block (Control) (A1P)
- Y1E : Electronic expansion valve (Main)
- Y2E : Electronic expansion valve (injection)
- Y1S : Solenoid valve (Main)
- Y2S : Solenoid valve (Accumulator oil return)
- Z1C-24C : Noise filter (ferrite core)
- Z1F : Noise filter (with surge absorber) (A2P)



- Notes:
- 1 Lay-out, illustrations and letter size = this drawing.
 - 2 Printing: Silkscreen printing black
 - 3 Add a slit on the backside of the sticker.



- 4 Unspecified tolerances: +/- 1
- 5 For material specifications refer to: AD150142

Notes:

1. This wiring diagram only applies to the outdoor unit.
2. Field wiring
3. Refer to the installation manual, for connection wiring to indoor-outdoor transmission F1 - F2, outdoor-outdoor transmission F1 - F2.
4. How to use BS1-B53 switch, refer to the installation manual.
5. When operating, do not short circuit for protection device. (S1PH)
6. Colours: BLK: Black, RED: Red, BLU: Blue, WHT: White, GRN: Green

3D094435D


10 External connection diagrams

10 - 1 External Connection Diagrams

RXYSQ8-12TY1

External connection diagram


VRV indoor unit




Notes

1. All wiring, components and materials to be procured on-site must comply with the applicable legislation.
2. Use copper conductors only.
3. For more details, refer to the wiring diagram of the unit.
4. Install a circuit breaker for safety.
5. All field wiring and components must be provided by an authorised electrician.
6. Unit has to be grounded in compliance with the applicable legislation.
7. The wiring shown is a general points-of-connection guide and is not intended to include all details for a specific installation.
8. Make sure to install the switch and the fuse to the power line of each equipment.
9. Install a main switch to (if necessary) immediately interrupt all the system's power sources.
10. If there exists the possibility of reversed phase, loose phase or momentary blackout, or if the power goes on and off while the product is operating, attach a reversed phase protection circuit locally.
11. Running the product in reversed phase may break the compressor and other parts.

BP box + RA/SA indoor unit



Power source is supplied to each BP box individually.




Power source is connected in series between the units.

10094669

11 Sound data

11 - 1 Sound Power Spectrum


RXYSQ8TY1



Notes
 - dBA = A-weighted sound power level (A scale according to IEC).
 - Reference acoustic intensity 0dB = 10E-6μW/m²
 - Measured according to ISO 3744

3D098240

RXYSQ10TY1



Notes
 - dBA = A-weighted sound power level (A scale according to IEC).
 - Reference acoustic intensity 0dB = 10E-6μW/m²
 - Measured according to ISO 3744


3D098241

11 Sound data

11 - 1 Sound Power Spectrum

11

RXYSQ12TY1




Notes
 - dBA = A-weighted sound power level (A scale according to IEC).
 - Reference acoustic intensity 0dB = 10E-6μW/m²
 - Measured according to ISO 3744

3D098242

11 Sound data


11 - 2 Sound Pressure Spectrum

RXYSQ8TY1




Notes

- Data is valid at free field condition.
- Data is valid at nominal operation condition.
- dBA = A-weighted sound pressure level (A scale according to IEC).
- Reference acoustic pressure 0 dB = 20 μ Pa




3D098245

RXYSQ10TY1



Notes

- Data is valid at free field condition.
- Data is valid at nominal operation condition.
- dBA = A-weighted sound pressure level (A scale according to IEC).
- Reference acoustic pressure 0 dB = 20 μ Pa




3D098246

11 Sound data

11 - 2 Sound Pressure Spectrum


11

RXYSQ12TY1



Notes

- Data is valid at free field condition.
- Data is valid at nominal operation condition.
- dBA = A-weighted sound pressure level (A scale according to IEC).
- Reference acoustic pressure 0 dB = 20 μ Pa



3D098247

12 Installation

12 - 1 Installation Method

RXYSQ8TY1


Required installation space

The unit of the values is mm.


1. Where there is an obstacle on the suction side:

(a) No obstacle above


- (1) Stand-alone installation
- Obstacle on the suction side only



- Obstacle on both sides




- (2) Series installation (2 or more) (note)
- Obstacle on both sides




(b) Obstacle above, too


- (1) Stand-alone installation
- Obstacle on the suction side, too



- Obstacle on the suction side and both sides




- (2) Series installation (2 or more) (note)
- Obstacle on the suction side and both sides




2. Where there is an obstacle on the discharge side:

(a) No obstacle above

- (1) Stand-alone installation




- (2) Series installation (2 or more) (note)




(b) Obstacle above, too

- (1) Stand-alone installation



- (2) Series installation (2 or more) (note)




3. Where there are obstacles on both suction and discharge sides:

Pattern 1


Where the obstacles on the discharge side is higher than the unit:
(There is no height limit for obstructions on the intake side.)

(a) No obstacle above

- (1) Stand-alone installation



- (2) Series installation (2 or more) (note)



3D068442T

12 - 1 Installation Method


12

Required installation space	1000 mm (39.4 in.)
-----------------------------	--------------------


The unit of the values is mm.

(a) No obstacle above


- Obstacle on the suction side only



- Obstacle on both sides




- (2) Series installation (2 or more) (note)
- Obstacle on both sides




(1) Stand-alone installation


- Obstacle on the suction side, too



- Obstacle on the suction side and both sides




- (2) Series installation (2 or more) (note)
 - Obstacle on the suction side and both sides




(a) No obstacle above


- (1) Stand-alone installation




- (2) Series installation (2 or more) (note)



(1) Stand-alone installation



- (2) Series installaton (2 or more) (note)




Pattern 1


Where the obstacles on the discharge side is higher than the unit:
(There is no height limit for obstructions on the intake side.)

(a) No obstacle above

- (1) Stand-alone installation



- (2) Series installation (2 or more) (note)



28

12 Installation

12 - 2 Refrigerant Pipe Selection

RXYSQ-TY1

VRV4-S Heat pump Piping restrictions :3/3-

System pattern Allowed connection ratio (CR) Other combinations are not allowed.	Total		Allowed capacity		
	Capacity	Maximum allowed amount of connectable indoor units (-VRV, RA, AHU-) Excluding -BP- units and including -EXV- kits.	VRV DX indoor unit	-RA DX- indoor unit	Air handling unit (AHU)
-VRV DX- indoor units only	50~130%	Maximum -64-	50~130%	-	-
-RA DX- indoor units only	80~130%	Maximum -32- (1)	-	80~130%	-
-VRV DX- indoor unit + -AHU- Mix	50~110% (3)	Maximum -64- (2)	50~110%	-	0~110%
-AHU- only Pair + multi (4)	90~110% (3)	Maximum -64- (2)	-	-	90~110%

Notes

- There is no restriction on the number of connectable -BP- boxes.
- EKEXV- kits are also considered indoor units.
- Restrictions regarding the air handling unit capacity
- Pair AHU = system with 1 air handling unit connected to one outdoor unit
Multi AHU = system with multiple air handling units connected to one outdoor unit

About ventilation applications

- FXMQ_MF- units are considered air handling units, following air handling unit limitations.
 - Maximum connection ratio when combined with -VRV DX- indoor units: -CR ≤ 30-%.
 - Maximum connection ratio when only air handling units are connected: -CR ≤ 100-%.
 - Minimum connection ratio when only -FXMQ_MF- units are connected: -CR ≥ 50-%
For information on the operation range, refer to the documentation of the -FXMQ_MF- unit.
- Biddle- air curtains are considered air handling units, following air handling unit limitations:
For information on the operation range, refer to the documentation of the -Biddle- unit.
- EKEXV + EKEQ- units combined with an air handling unit are considered air handling units, following air handling unit limitations.
For information on the operation range, refer to the documentation of the -EKEXV-EKEQ- unit.
- VKM- units are considered to be regular -VRV DX- indoor units.
For information on the operation range, refer to the documentation of the -VKM- unit.
- Because there is no refrigerant connection with the outdoor unit (only communication F1/F2), -VAM- units do not have connection limitations.
However, since there is communication via F1/F2, count them as regular indoor unit when calculating the maximum allowed number of connectable indoor units.

3D097984B

RXYSQ-TY1

VRV4-S Heat pump Piping restrictions :1/3-

For the reference drawing, see page :2/3-.

		Maximum piping length		Maximum height difference		Total piping length
		Longest pipe (A+[B,D+E,H]) Actual / (Equivalent)	After first branch (B,D+E,H) Actual	Indoor-to-outdoor (H1) Outdoor above indoor / (indoor above outdoor)	Indoor-to-indoor (H2)	
Standard	RXYSQ4~6TMV1B	70/(90)m	40m	30/(30)m	15m	300m
	RXYSQ4~6T7(V/Y)1B	120/(150)m	40m	50/(40)m	15m	300m
	RXYSQ4~6T8(V/Y)1B	100/(130)m	40m	50/(40)m	15m	300m
	RXYSQ8TMY1B	120/(150)m	40m	50/(40)m	15m	300m
-VRV DX- indoor units only	RXYSQ10~12TMY1B	35/(45)m	40m	30/(30)m	15m	140m
	RXYSQ4~6TMV1B	65/(85)m	40m	30/(30)m	15m	140m
	RXYSQ4~6T7(V/Y)1B	80/(100)m	40m	30/(30)m	15m	140m
	RXYSQ8TMY1B	80/(100)m	40m	30/(30)m	15m	140m
-RA- connection	RXYSQ10~12TMY1B	50/(55)m (1)	-	40/(40)m	-	-
	Multi (2)	50/(55)m (1)	40m	40/(40)m	15m	300m
	Mix (3)	50/(55)m (1)	40m	40/(40)m	15m	300m
	Air handling unit (-AHU-) connection					

Notes

- The allowable minimum length is 5- m.
- Multiple air handling units (-AHU-)(-EKEXV- + -EKEQ- kits).
- Mix of air handling units (-AHU-) and -VRV DX- indoor units.


3D097984B

12 Installation

12 - 2 Refrigerant Pipe Selection

RXYSQ-TY1

VRV4-S Heat pump Piping restrictions ·2/3·



Notes

1. Schematic indication
Illustrations may differ from the actual appearance of the unit.
2. This is only to illustrate piping length limitations.
Refer to combination table ·3D097983· for details about the allowed combinations.

		Allowed piping length		Maximum height difference	
		·BP· to ·RA· (E)	·EXV· to ·AHU· (J)	·BP· to ·RA· (H3)	·EXV· to ·AHU· (H4)
·RA· connection		2~15m	-	5m	-
Air handling unit (AHU) Connection	Pair	-	≤5m	-	5m
	Multi ⁽¹⁾	-	≤5m	-	5m
	Mix ⁽²⁾	-	≤5m	-	5m

Notes

1. Multiple air handling units (·AHU·)(·EKEV· + ·EKEQ· kits).
2. Mix of air handling units (·AHU·) and ·VRV DX· indoor units.

3D097984B

13 Operation range


13 - 1 Operation Range

RXYSQ8-12TY1


Notes

- These figures assume the following operation conditions
Indoor and outdoor units
Equivalent piping length: 5m
Level difference: 0m
- Depending on operation and installation conditions, the indoor unit can change over to freeze-up operation (indoor de-icing).
- To reduce the freeze-up operation (indoor de-icing) frequency, it is recommended to install the outdoor unit in a location not exposed to wind.
- Operation range is valid in case direct expansion indoor units are used.
If other indoor units are used, refer to the documentation of the respective indoor units.
- Unit operation is possible, but no guaranteed capacity
- If the unit is selected to operate at ambient temperatures $< -5^{\circ}\text{C}$ for 5 days or more, with relative humidity levels $> 95\%$, it is recommended to apply a Daikin range specifically designed for such application.
For more information, contact your dealer.

Cooling



Heating



3D094665A

14 Appropriate Indoors

14 - 1 Appropriate Indoors

RXYSQ-TY1
RXYSQ-TY9
RXYSQ-TV9
RXYSQ-TV1

Recommended indoor units for ·RXYSQ*T* AND RXYSQ*T*· outdoor units

HP	4	5	6	8	10	12
	3xFSQ25 1xFSQ32	4xFSQ32	2xFSQ32 2xFSQ40	4xFXMQ50	4xFXMQ63	6xFXMQ50

For details about the allowed combinations, see the engineering databook.

Appropriate indoor units for ·RXYSQ*T* AND RXYSQ*T*· outdoor units

Covered by ·ENER LOT21·

FXFQ20-25-32-40-50-63-80-100-125
FXZQ15-20-25-32-40-50
FXCQ20-25-32-40-50-63-80-125
FXKQ25-32-40-63
FXDQ15-20-25-32-40-50-63
FXSQ15-20-25-32-40-50-63-80-100-125-140
FXMQ50-63-80-100-125-200-250
FXAQ15-20-25-32-40-50-63
FXHQ32-63-100
FXUQ71-100
FXNQ20-25-32-40-50-63
FXLQ20-25-32-40-50-63


Outside the scope of ·ENER LOT21·

EKEXV50-63-80-100-125-140-200-250 + EKEQM / EKEQF
VKM50-80-100
CYVS100-150-200-250
CYVM100-150-200-250
CYVL100-150-200-250

Covered by ·ENER LOT10·

FTXJ25-35-50
FTXA20-25-35-42-50
FTXM20N-25N-35N-42N-50N-60N-71N
FTXM20R-25R-35R-42R-50R-60R-71R
CTXM15N
CTXM15R
FLXS25-35-50-60
FVXM25F-35F-50F
FVXG25-35-50
FNA25-35-50-60
FDXM25-30-50-60
FFA25-35-50-60
FCAG35-50-60-71
FHA35-50-60-71
FBA35-50-60-71
FVXM25-35-50
CVXM20A
FVXM25A-35A-50A

3D113977E



EEDEN22

02/2022



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.